


**TUNING FORK CRYSTAL UNITS (SMD • Plastic Package)**

RoHS compliant

**CM200C • CM250C**


3000pcs/reel




**FEATURES**

- Molding a heat resistant cylinder with resin.
- Most appropriate for clock source for portable equipment with low power consumption.

**DIMENSION [mm]**



**SOLDER PAD LAYOUT [mm]**



**STANDARD SPECIFICATIONS**

Item	Model	CM200C	CM250C	Conditions
Nominal Frequency	$f_0$	32.768kHz	30kHz~100kHz	Need to contact us for the available frequency in CM250C
Frequency Tolerance	$\Delta f/f_0$	$\pm 20\text{ppm}$	$\pm 30\text{ppm}$	at 25°C
Load capacitance	$C_L$	12.5pF		Need to specify your requirement
Operating Temperature Range	$T_{OPR}$	-40°C~+85°C		
Storage Temperature Range	$T_{STR}$	-55°C~+125°C		
Turnover Temperature	$T_M$	25°C $\pm$ 5°C		
Temperature Coefficient	$\beta$	-0.034 $\pm$ 0.006ppm/°C <sup>2</sup>		
Motional (series) resistance	$R_1$	50K $\Omega$ Max.		at 25°C
Level of drive	DL	1 $\mu$ W Max.		
Aging (first year)	$\Delta f/f_0$	$\pm 3\text{ppm}$ Max.	$\pm 5\text{ppm}$ Max.	25°C $\pm$ 3°C
Shunt capacitance	$C_0$	1.35pF Typ.	0.8pF ~ 1.7pF Typ.	Depend on frequency